

Graph Positional Autoencoders as Self-supervised Learners

Yang Liu*, Deyu Bo*, Wenxuan Cao, Yuan Fang, Yawen Li, Chuan Shi†







^{*} Both authors contributed equally to this research. † Corresponding author.




Background Masked Graph Autoencoders






Maked Graph Autoencoders (Masked GAEs) follow a corruption-reconstruction framework, which learns graph representations by recovering the missing information of the incomplete corruption reconstruction input graphs.



Pre-training of Maked Graph Autoencoders



Fine-tuning for downstream task (e.g. node classification)


Background Frequency Bases in Graphs





Eigenvectors of the graph Laplacian represent different frequencies, acting as frequency bases in the spectral domain.

Given eigen-decomposition $Lu_k = \lambda_k u_k$ with $u_k^{\mathsf{T}} u_k = 1$, we have $u_k^{\mathsf{T}} Lu_k = u_k^{\mathsf{T}} \lambda_k u_k = \lambda_k$. Since $u_k^{\mathsf{T}} L u_k = \sum_{(i,j) \in \mathcal{E}} (u_{i,k} - u_{j,k})^2$, we obtain $\sum_{(i,j) \in \mathcal{E}} (u_{i,k} - u_{j,k})^2 = \lambda_k$. Therefore, λ_k reflects the frequency magnitude of u_k over the graph.



Motivation







Limitations of existing methods:

Existing masked GAEs tend to focus on reconstructing low-frequency information of graphs

while overlooking high-frequency information.

	C	Corrupti	on	Reconstruction			
Model	Feature	Edge	Position	Feature	Edge	Other	
GraphMAE [18]	✓	-	-	✓	-	-	
StructMAE [32]	\checkmark	-	-	\checkmark	-	-	
AUG-MAE [59]	\checkmark	-	-	\checkmark	-	-	
S2GAE [50]	-	\checkmark	-	-	\checkmark	-	
SeeGera [30]	\checkmark	\checkmark	-	\checkmark	\checkmark	-	
Bandana [77]	-	\checkmark	-	-	\checkmark	-	
MaskGAE [28]	-	\checkmark	-	\checkmark	-	Degree	
GiGaMAE [45]	\checkmark	\checkmark	-	-	-	Latent	
GraphPAE	✓	_	✓	✓	_	Position	






 How can we design the corruption and reconstruction objectives to exploit the diverse frequency information?

Inspired by Spectral Theory





- The eigenvectors of graph Laplacian correspond to different frequencies in the graph signal processing.
- Directly perturbing eigenvectors can explicitly corrupt corresponding frequency information in the graph.





Incorporating eigenvector corruption-reconstruction into masked GAEs.


- Two main challenge of reconstructing the eigenvectors:
 - ✓ GNN Expressivity: Eigenvectors represent global structural patterns, which cannot be easily approximated by GNNs, whose expressiveness is bounded by the 1-WL test.
 - ✓ Eigenvector Ambiguity: Eigenvectors suffer from sign- and basis- ambiguity issues. Directly reconstructing eigenvectors leads to non-unique solutions, thereby affecting the robustness of GAEs.



GraphPAE Overall Framework







4

GraphPAE Data Corruption





Feature Masking.

Randomly sampling a subset of nodes $\widetilde{\mathcal{V}} \subset \mathcal{V}$ and reset their features. The corrupted feature matrix $\widetilde{\mathbf{X}}$ is defined as:

$$\widetilde{\mathbf{X}}_{i} = \begin{cases} \mathbf{x}_{[M]}, & \text{if } v_{i} \in \widetilde{\mathcal{V}} \\ \mathbf{X}_{i}, & \text{if } v_{i} \notin \widetilde{\mathcal{V}} \end{cases}$$


Position Offsetting.

Adding random offsets to node position:


$$\widetilde{\mathbf{U}}_{i} = \begin{cases} \mathbf{U}_{i} + \delta, & \text{if } v_{i} \in \widetilde{\mathcal{V}} \\ \mathbf{U}_{i}, & \text{if } v_{i} \notin \widetilde{\mathcal{V}} \end{cases} \quad \delta \in \mathbb{R}^{K} \text{ is sampled from } \mathcal{U}\left(-\mu_{p}, \mu_{p}\right)$$

Relative Positional Encoding.

$$\mathbf{P}_{i,j} = \begin{cases} \|\mathbf{U}_i - \mathbf{U}_j\|_2, & \text{if } \mathbf{A}_{i,j} = 1\\ 0, & \text{otherwise} \end{cases}$$



Feature Masking



Position Offsetting

GraphPAE Encoder





Overall formulation.


$$\begin{aligned} \mathbf{X}_{i}^{(l+1)}, \mathbf{P}_{i}^{(l+1)} &= f_{\mathrm{enc}}^{(l+1)} \left(\mathbf{X}_{i}^{(l)}, \left\{ \mathbf{X}_{j}^{(l)} \right\}_{j \in \mathcal{N}_{i}}, \mathbf{P}_{i}^{(l)} \right) \\ \mathbf{P}_{i,j}^{(0)} &= \mathrm{MLP} \left(\left[G(\mathbf{P}_{i,j}; \mu_{1}, \sigma), \cdots, G(\mathbf{P}_{i,j}; \mu_{d}, \sigma) \right] \right) \quad \mathbf{X}_{i}^{(0)} &= \mathrm{MLP} \left(\mathbf{X}_{i} \right). \\ G(\mathbf{P}_{i,j}; \mu_{k}, \sigma) &= \exp \left(- \left(\mathbf{P}_{i,j} - \mu_{k} \right)^{2} / 2\sigma^{2} \right) \end{aligned}$$


Feature Path: PE-enhanced MPNNs.

$$\begin{split} &\alpha_{i,j}^{(l)} = f_{\text{att}}\left(\mathbf{X}_i^{(l)}, \mathbf{X}_j^{(l)}\right), \quad \alpha_{i,j}^{(l)} \in \mathbb{R}^d, \\ &\mathbf{X}_i^{(l+1)} = \sum_{j \in \mathcal{N}_i} \left(\alpha_{i,j}^{(l)} + \mathbf{P}_{i,j}^{(l)}\right) \odot \text{MLP}\left(\mathbf{X}_j^{(l)}\right), \end{split}$$

Position Path: Refine Node Positions.

$$\mathbf{P}_{i,j}^{(l+1)} = \alpha_{i,j}^{(l)} + \mathbf{P}_{i,j}^{(l)}.$$





GraphPAE Decoder



 $P \in \mathbb{R}^{|\mathcal{E}|}$

 $P' \in \mathbb{R}^{|\mathcal{E}|}$



Feature Reconstruction.

$$\mathbf{X}_{i}^{'} = f_{\text{dec}}^{X} \left(\widetilde{\mathbf{X}}_{i}^{(L)} \right),$$


$$\mathcal{L}_{\text{feat}} = \frac{1}{|\widetilde{\mathcal{V}}|} \sum_{v_{i} \in \widetilde{\mathcal{V}}} \left(1 - \frac{\mathbf{X}_{i}^{T} \mathbf{X}_{i}^{'}}{\|\mathbf{X}_{i}\| \cdot \|\mathbf{X}_{i}^{'}\|} \right)^{\gamma},$$

Position Reconstruction.

$$\mathbf{P}'_{i,j} = f_{\text{dec}}^{P} \left(\widetilde{\mathbf{P}}_{i,j}^{(L)} \right)$$

$$\mathcal{L}_{\text{pos}}^{i,j} = \begin{cases} \frac{\left(\mathbf{P}'_{i,j} - \mathbf{P}_{i,j} \right)^{2}}{2}, & \text{if } |\mathbf{P}'_{i,j} - \mathbf{P}_{i,j}| < 1 \\ |\mathbf{P}'_{i,j} - \mathbf{P}_{i,j}| - \frac{1}{2}, & \text{otherwise} \end{cases}$$

$$\mathcal{L}_{\text{pos}} = \frac{1}{\sum_{v_{i} \in \widetilde{\mathcal{V}}} |\mathcal{N}_{i}|} \sum_{v_{i} \in \widetilde{\mathcal{V}}, j \in \mathcal{N}_{i}} \mathcal{L}_{\text{pos}}^{i,j}$$



 $\widetilde{\mathbf{P}}^{(L)} \in \mathbb{R}^{|\mathcal{E}| \times d_p}$

 $X \in \mathbb{R}^{N \times d}$

 $\widetilde{P} \in \mathbb{R}^{|\mathcal{E}|}$

Position Offsetting

• Overall Loss Function. $\mathcal{L} = \mathcal{L}_{\text{feat}} + \alpha \mathcal{L}_{\text{pos}}$

 L_{pos}



Experiments Performance of Node Classification





		Small C	Large Graphs			
Dataset	BlogCatalog	Chameleon	Squirrel	Actor	arXiv-year	Penn94
Supervised	80.52±2.10	80.02±0.87	71.91±1.03	33.93±2.47	46.02±0.26	81.53±0.55
DGI	72.07±0.16	43.83±0.14	34.56±0.10	27.98±0.09	-	-
BGRL	79.74±0.46	61.24±1.07	43.24±0.52	26.61±0.57	41.43±0.04	63.31±0.49
MVGRL	63.24±0.94	73.19 ± 0.42	60.09 ± 0.44	34.64±0.20	-	-
CCA-SSG	74.00 ± 0.28	75.00±0.75	61.58±1.98	27.79±0.58	40.78±0.01	62.63±0.20
Sp ² GCL	72.73±0.46	78.88±1.04	62.61±0.87	34.70 ± 0.92	39.09±0.02	68.80±0.45
VGAE	60.47±1.84	62.32±1.90	42.50±1.35	31.57±0.75	36.39±0.21	55.31±0.28
GraphMAE	79.90±1.13	79.50±0.57	61.13±0.60	32.15±1.33	40.30 ± 0.04	67.97 ± 0.21
GraphMAE2	77.34 ± 0.12	79.13±0.19	70.27 ± 0.88	34.48 ± 0.26	38.97 ± 0.03	67.86 ± 0.42
MaskGAE	73.10 ± 0.08	74.50 ± 0.87	68.53±0.44	33.44±0.34	40.59 ± 0.04	63.84 ± 0.03
S2GAE	75.76 ± 0.43	60.24±0.37	68.60±0.56	26.17±0.38	40.32±0.12	70.24 ± 0.09
AUG-MAE	82.03±0.69	70.10±1.88	62.57±0.67	33.42±0.38	37.10±0.13	69.90±0.43
GraphPAE	85.76±1.22	80.51±1.25	72.05±1.40	38.55±1.35	41.85±0.04	71.79±0.37

Table 1. Node classification results of different graph self-supervised learning.



Experiments Performance of Graph Prediction





Task	Regres	ssion (Metric: R	MSE ↓)	Classification			
Dataset	aset molesol molipo molfreesolv		molbace	molbace molbbbp		moltocx21	
Supervised	1.173±0.057	0.757±0.018	2.755±0.349	80.42±0.96	68.17±1.48	88.14±2.51	74.91±0.51
InfoGraph	1.344±0.178	1.005±0.023	10.005±8.147	73.64±3.64	66.33±2.79	64.50±5.32	69.74±0.57
GraphCL	1.272 ± 0.089	0.910 ± 0.016	7.679 ± 2.748	73.32±2.70	68.22±2.19	74.92 ± 4.42	72.40 ± 1.07
MVGRL	1.433 ± 0.145	0.962 ± 0.036	9.024 ± 1.982	74.88±1.43	67.24±3.19	73.84±2.75	70.48 ± 0.83
JOAO	1.285 ± 0.121	0.865 ± 0.032	5.131±0.782	74.43±1.94	67.62±1.29	71.28 ± 4.12	71.38±0.92
Sp^2GCL	1.235±0.119	0.835 ± 0.026	4.144±0.573	78.76±1.43	68.72±1.53	80.88±3.86	73.06±0.75
GraphMAE	1.050±0.034	0.850±0.022	2.740±0.233	79.14±1.31	66.55±1.78	80.56±5.55	73.84±0.58
GraphMAE2	1.225 ± 0.081	0.885 ± 0.019	2.913±0.293	80.74±1.53	67.67±1.44	75.75±3.65	72.93±0.69
StructMAE	1.499 ± 0.043	1.089 ± 0.002	2.568 ± 0.262	77.75 ± 0.42	65.66±1.16	79.42±4.56	71.13±0.61
AUG-MAE	1.248±0.026	0.917±0.013	2.395±0.158	78.54±2.49	67.05±0.63	82.66±1.98	74.33±0.07
GraphPAE	1.015±0.045	0.810±0.018	2.058±0.188	81.11±1.24	68.56±0.71	82.69±3.39	74.46±0.54

Table 2. Graph regression and classification results of different graph self-supervised learning on OGB datasets.

Experiments Ablation Studies





Exp	Corru	pt Info.	Recon Info.		Dual-Path	Node-level		Graph-level		
No.	Feature	Position	Feature	Position		Blog (↑)	Squirrel (†)	Bace (†)	Bbbp (†)	Freesolv (\lambda)
a	✓	✓	✓			82.8±1.7	66.4±1.6	78.4±1.2	66.4±1.7	2.79±0.40
b	\checkmark	\checkmark	\checkmark	\checkmark		83.5±1.0	68.5±0.9	78.9±2.1	66.8±0.6	2.44±0.36
c	\checkmark		\checkmark		\checkmark	84.6±1.6	71.3±0.9	79.4±3.4	67.7±0.9	2.20 ± 0.14
d	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	85.8±1.2	72.1±1.4	81.1±1.2	68.6±0.7	2.06±0.19

Table 3. Ablation studies of position reconstruction and framework design.




Figure 1: Influence of loss weight \mathcal{L}_{pos} and the number of eigenvectors K.







Thanks

Paper



Q&A



liuyangjanet@bupt.edu.cn

Code